Question 1(a) [3 marks]

List four microwave frequency bands with their frequency range and applications.

Answer:

Band	Frequency Range	Applications
L-band	1-2 GHz	GPS, Mobile communication
S-band	2-4 GHz	WiFi, Bluetooth, Radar
C-band	4-8 GHz	Satellite communication
X-band	8-12 GHz	Military radar, Weather radar

Mnemonic: "Little Satellites Communicate eXcellently"

Question 1(b) [4 marks]


Explain the impedance matching process using a single stub.

Answer:

Single stub matching removes reflections by adding a **short-circuited stub** at specific distance from load.

Process:

- Stub length: Provides reactive impedance
- Stub position: Calculated from load using Smith chart
- Matching condition: Real part = Z₀, imaginary part = 0



Mnemonic: "Stub Positioned for Perfect Matching"

Question 1(c) [7 marks]

State characteristics of lossless transmission line and obtain the general equation for a two-wire transmission line.

Answer:

Characteristics of Lossless Line:

• **No power loss**: R = 0, G = 0

• Constant amplitude: No attenuation

• Phase delay only: Signal delayed but not weakened

• Standing wave pattern: Due to reflections

General Equations:

For voltage: $V(z) = V_+e^{-\gamma z} + V_-e^{-\gamma z}$

For current: $I(z) = (V_{+}/Z_{0})e^{(-\gamma z)} - (V_{-}/Z_{0})e^{(\gamma z)}$

Where:

• $y = \alpha + i\beta$ (propagation constant)

• $Z_0 = \sqrt{(L/C)}$ (characteristic impedance)

• For lossless line: $\alpha = 0$, $\gamma = j\beta$

Mnemonic: "Lossless Lines Love Low Loss"

Question 1(c) OR [7 marks]

Define standing wave. Draw and explain the standing wave pattern for short circuit and open circuit line.

Answer:


Standing Wave: Fixed pattern formed by **forward and reflected waves** interfering constructively and destructively.

Short Circuit Line:

- Current maximum at short circuit
- Voltage minimum at short circuit
- Distance between minima: λ/2

Open Circuit Line:

- Voltage maximum at open circuit
- Current minimum at open circuit
- Distance between maxima: λ/2




Mnemonic: "Short Circuits Current, Open Circuits Voltage"

Question 2(a) [3 marks]

Draw and explain the working of Magic TEE.

Answer:

Magic TEE combines E-plane and H-plane tees with four ports providing isolation between opposite ports.



Working:

• E-arm and H-arm: Isolated from each other

• **Sum port**: Adds signals from collinear arms

• **Difference port**: Subtracts signals

Mnemonic: "Magic Tee Mixes Modes"

Question 2(b) [4 marks]

Explain the working of Hybrid ring.

Answer:

Hybrid Ring is a **circular waveguide** with **four ports** spaced at specific intervals for power division and isolation.

Construction:

• Ring circumference: 1.5λ

• **Port spacing**: λ/4 between adjacent ports

• Matched impedance: Each port matched to Z₀

Working:

• Power splitting: Input splits equally between two output ports

• Isolation: Opposite ports are isolated

• Phase difference: 180° between output ports

Mnemonic: "Ring Runs Round for Power Sharing"


Question 2(c) [7 marks]

Explain the construction and working principle of "CIRCULATOR". List its applications.

Answer:

Construction:

- Three-port device with ferrite material
- Permanent magnet creates magnetic field
- Y-junction waveguide structure



Working Principle:

- Faraday rotation: Magnetic field rotates wave polarization
- Unidirectional flow: Power flows in one direction only
- Non-reciprocal: Different behavior for opposite directions

Applications:

Radar systems: Isolates transmitter from receiver

• Communication: Antenna sharing for TX/RX

• Microwave amplifiers: Prevents feedback

Mnemonic: "Circulator Circles Clockwise Continuously"

Question 2(a) OR [3 marks]

Compare rectangular waveguide and circular waveguide.

Answer:

Parameter	Rectangular	Circular
Cross-section	Rectangle	Circle
Dominant mode	TE ₁₀	TE ₁₁
Cutoff frequency	Easy calculation	Complex calculation
Manufacturing	Simple	Moderate
Power handling	Lower	Higher


Mnemonic: "Rectangles are Regular, Circles are Complex"

Question 2(b) OR [4 marks]

Draw and explain the working of a directional coupler.

Answer:

Directional Coupler samples **forward power** while providing isolation from reflected power.



Working:

- Coupling factor: Determines power extracted (10-20 dB typical)
- Directivity: Isolates forward from reverse power
- Insertion loss: Minimal loss in main line

Parameters:

- $C = 10 log(P_1/P_3)$ (Coupling factor)
- $D = 10 log(P_3/P_4)$ (Directivity)

Mnemonic: "Coupler Couples Carefully in Correct Direction"

Question 2(c) OR [7 marks]

Explain the construction and working principle of "Travelling Wave Tube". List its applications.

Answer:


Construction:

• Electron gun: Emits electron beam

• Helix structure: Slows down RF wave

• Collector: Collects spent electrons

• Magnetic focusing: Keeps beam focused



Working Principle:

- **Velocity synchronization**: Electron velocity ≈ RF wave velocity
- Energy transfer: Electrons give energy to RF wave
- Continuous interaction: Along entire helix length

Applications:

- Satellite communication: High power amplification
- Radar transmitters: High gain amplification
- Electronic warfare: Jamming systems

Mnemonic: "TWT Transfers Tremendous power Through Travel"

Question 3(a) [3 marks]

Explain the Indirect method for higher VSWR measurement.

Answer:

Indirect Method measures **high VSWR** by using **attenuator** to reduce signal level for accurate measurement.

Procedure:

- Insert calibrated attenuator (10-20 dB)
- Measure reduced VSWR (VSWR₂)
- Calculate actual VSWR: VSWR₁ = VSWR₂ × Attenuator ratio

Formula: VSWR_actual = VSWR_measured × 10^(Attenuation/20)

Mnemonic: "Indirect method uses Intermediate Attenuation"

Question 3(b) [4 marks]

Write and explain the frequency limitations of conventional tubes.

Answer:

Frequency Limitations:

- Transit time effect: Electron transit time becomes significant
- Interelectrode capacitance: Limits high frequency response
- Lead inductance: Parasitic inductance reduces gain
- Skin effect: Current flows on surface only

Effects:

- Reduced gain: At frequencies above fα
- Increased noise: Due to shot noise
- Phase shift: Delays signal processing

Solutions:

Reduce electrode spacing

- Use special tube designs
- Employ cavity resonators

Mnemonic: "Transit Time Troubles Traditional Tubes"

Question 3(c) [7 marks]

Explain construction and working of Two cavity klystron with applegate diagram. List its advantages.

Answer:

Construction:

• Electron gun: Produces electron beam

• Input cavity: Velocity modulates beam

• Drift region: Beam bunching occurs

• Output cavity: Extracts RF energy

• Collector: Collects electrons

Applegate Diagram:

Working:

• Velocity modulation: Input cavity varies electron velocity

• **Density modulation**: Electrons bunch in drift space

• Energy extraction: Bunched beam transfers energy to output cavity

Advantages:

• **High power output**: Several kilowatts

• High efficiency: 40-60%

• Low noise: Better than semiconductor devices

• Stable operation: Excellent frequency stability

Mnemonic: "Klystron Kicks with Kinetic Bunching"

Question 3(a) OR [3 marks]

Explain construction and working of BWO.

Answer:

BWO (Backward Wave Oscillator) uses backward wave interaction for oscillation.

Construction:

• Electron gun: Emits electron beam

• Slow wave structure: Helix or coupled cavities

• **Collector**: At input end

• Output: From input end

Working:

• Backward wave: Travels opposite to electron beam

• Negative resistance: Beam provides energy to backward wave

• **Oscillation**: When gain > losses

Mnemonic: "BWO goes Backward While Oscillating"

Question 3(b) OR [4 marks]

Explain hazards due to microwave radiation.

Answer:

Types of Hazards:

• HERP: Hazards of Electromagnetic Radiation to Personnel

• HERO: Hazards of Electromagnetic Radiation to Ordnance

• HERF: Hazards of Electromagnetic Radiation to Fuel

Effects:

• Thermal heating: Tissue heating at high power

• Eye damage: Cataract formation

• Reproductive effects: Potential fertility issues

• Pacemaker interference: Electronic device malfunction

Protection:

• Power density limits: < 10 mW/cm²

Safety distances: Far field calculations

• Warning signs: Radiation hazard markers

• Personal monitors: RF exposure meters

Mnemonic: "Microwaves Make Multiple Medical Maladies"

Question 3(c) OR [7 marks]

Explain construction and working of magnetron with neat sketch. List its applications.

Answer:


Construction:

• Circular cathode: Central hot cathode

• Cylindrical anode: With resonant cavities

• Permanent magnet: Provides axial magnetic field

• Output coupling: Loop or probe



Working:

- Electron cloud: Forms in interaction space
- Cycloid motion: Due to E and B fields
- Resonant cavities: Determine operating frequency
- π -mode oscillation: Alternate cavities have opposite phase

Applications:

• Microwave ovens: 2.45 GHz heating

• Radar systems: High power pulses

• Industrial heating: Material processing

• Medical diathermy: Therapeutic heating

Mnemonic: "Magnetron Makes Microwaves Magnificently"

Question 4(a) [3 marks]

Explain working of P-i-N diode.

Answer:

P-i-N Diode has **intrinsic layer** between P and N regions, acting as **voltage-controlled resistor**.

Structure:

• P region: Heavily doped

• I region: Intrinsic (undoped)

• N region: Heavily doped

Working:

• **Forward bias**: Low resistance (1-10 Ω)

• **Reverse bias**: High resistance (>10 k Ω)

• **RF switch**: Controls microwave signals

• Variable attenuator: Resistance varies with DC bias

Mnemonic: "PIN controls Power IN Networks"

Question 4(b) [4 marks]

Explain the working of Varactor diode with sketch.

Answer:

Varactor Diode acts as voltage-controlled capacitor using junction capacitance variation.

Working:

- Reverse bias: Depletes junction, reduces capacitance
- Bias voltage: Controls capacitance value
- Capacitance ratio: Typically 3:1 to 10:1
- Frequency tuning: Used in oscillators and filters

Applications:

• VCO tuning: Voltage controlled oscillators

• AFC circuits: Automatic frequency control

• Parametric amplifiers: Low noise amplification

Mnemonic: "Varactor Varies Capacitance with Voltage"

Question 4(c) [7 marks]

Explain construction and working of Tunnel Diode and explain tunneling phenomenon in detail. List its applications.

Answer:

Construction:

• Heavily doped P-N junction: Both sides degenerately doped

• Thin junction: ~10 nm width

• Quantum tunneling: Electrons tunnel through barrier

Tunneling Phenomenon:

• Quantum effect: Electrons pass through energy barrier

• Band overlap: Conduction band overlaps valence band

• Probability function: Tunneling probability depends on barrier width

• No thermal activation: Occurs at room temperature

Working:

Forward bias 0-Vp: Current increases (tunneling)

• **Vp to Vv**: Negative resistance region

• **Beyond Vv**: Normal diode operation

Applications:

• High-speed switching: Picosecond switching

• Oscillators: Microwave frequency generation

• Amplifiers: Low noise amplification

• Memory circuits: Bistable operation

Mnemonic: "Tunnel Diode Tunnels Through barriers Terrifically"

Question 4(a) OR [3 marks]

Describe the operation of IMPATT diode.

Answer:

IMPATT (Impact Avalanche Transit Time) diode uses **avalanche multiplication** and **transit time delay** for oscillation.

Operation:

• Avalanche zone: Impact ionization creates carriers

• **Drift zone**: Carriers drift with constant velocity

• Transit time: Provides 180° phase shift

• Negative resistance: Due to phase delay

Key parameters:

• Breakdown voltage: Typically 20-100V

• **Efficiency**: 10-20%

• Frequency range: 1-300 GHz

Mnemonic: "IMPATT Impacts with Avalanche Transit Time"

Question 4(b) OR [4 marks]

Explain the frequency up and down conversion concepts for parametric amplifier.

Answer:

Parametric Amplifier uses **time-varying reactance** for amplification and frequency conversion.

Up-conversion:

• Signal frequency: fs (input)

• Pump frequency: fp (much higher)

• Output frequency: fo = fp + fs

• Energy transfer: From pump to signal

Down-conversion:

• Signal frequency: fs (input)

• Pump frequency: fp

• Output frequency: fo = fp - fs

• Mixer operation: Frequency translation

Advantages:

• Low noise: Quantum-limited performance

• **High gain**: 20-30 dB typical

• Wide bandwidth: Several GHz

Mnemonic: "Parametric Pump Provides frequency conversion Plus gain"

Question 4(c) OR [7 marks]

Describe the construction and working principle of RUBY MASER. List its applications.

Answer:

Construction:


• Ruby crystal: Cr³⁺ ions in Al₂O₃ lattice

• Magnetic field: Strong DC magnetic field

• Microwave cavity: Resonant at signal frequency

• Pump source: High frequency klystron

• Cryogenic cooling: Liquid helium temperature



Working Principle:

• **Energy levels**: Cr³+ ions have three energy levels

• Population inversion: Pump creates more atoms in upper level

• Stimulated emission: Signal photons trigger emission

• **Coherent amplification**: Phase-coherent amplification

Three-level system:

• **Ground state**: E₁ (most populated)

• Intermediate state: E₂ (signal frequency)

• **Upper state**: E₃ (pump frequency)

Applications:

• Radio astronomy: Ultra-low noise receivers

• **Satellite communication**: Ground station amplifiers

Deep space communication: NASA tracking stations

• Research: Quantum electronics experiments


Mnemonic: "RUBY MASER Makes Amazingly Sensitive Electromagnetic Receivers"

Question 5(a) [3 marks]

Draw and explain the functional block diagram of MTI RADAR.

Answer:

MTI RADAR detects moving targets by comparing successive echoes and canceling fixed targets.



Components:

• STALO: Stable Local Oscillator

COHO: Coherent Oscillator

• Phase detector: Compares echo phases

• Canceller: Removes fixed target echoes

Mnemonic: "MTI Makes Targets Intelligible by Motion"

Question 5(b) [4 marks]

Compare RADAR with SONAR.

Answer:

Parameter	RADAR	SONAR
Wave type	Electromagnetic	Acoustic
Medium	Air/vacuum	Water
Speed	3×10 ⁸ m/s	1500 m/s
Frequency	GHz	kHz
Range	100+ km	10-50 km
Applications	Air/space	Underwater

Common features:

- Pulse-echo principle
- Range measurement
- Target detection

Mnemonic: "RADAR Radiates, SONAR Sounds"

Question 5(c) [7 marks]

Obtain the equation of maximum RADAR range. Explain the factors affecting the maximum radar range.

Answer:

RADAR Range Equation:

 $R_{max} = \sqrt[4]{[(P_t \times G^2 \times \lambda^2 \times \sigma) / (64\pi^3 \times P_{min} \times L)]}$

Where:

- **P_t**: Transmitter power (W)
- **G**: Antenna gain (dimensionless)
- λ: Wavelength (m)
- σ: Target cross-section (m²)
- **P_min**: Minimum detectable power (W)
- L: System losses (dimensionless)

Derivation steps:

- 1. Power density at target: $P_t \times G/(4\pi R^2)$
- 2. **Power intercepted**: $\sigma \times$ Power density
- 3. **Power at receiver**: Intercepted power \times G/(4 π R²)
- 4. Set equal to P_min and solve for R

Factors Affecting Range:

Increase Range:

• Higher transmitter power: R ∝ P_t^(1/4)

• Larger antenna gain: R ∝ G^(1/2)

• Larger target RCS: R ∝ σ^(1/4)

• Lower system losses: R ∝ L^(-1/4)

Decrease Range:

• Higher frequency: R ~ λ^(1/2)

• Atmospheric losses: Absorption and scattering

• Ground clutter: Interfering reflections

Mnemonic: "RADAR Range Requires Robust Power and Proper Parameters"

Question 5(a) OR [3 marks]

Describe the Doppler effect in CW Doppler RADAR.

Answer:

Doppler Effect causes **frequency shift** when target moves relative to RADAR.

Doppler Frequency:

 $f_d = (2 \times V_r \times f_0) / c$

Where:

- **V_r**: Radial velocity (m/s)
- **f_0**: Transmitted frequency (Hz)
- c: Speed of light (3×10⁸ m/s)

Characteristics:

• Approaching target: f_d positive

• Receding target: f_d negative

• Factor of 2: Due to two-way propagation

Mnemonic: "Doppler Detects Direction with Doubled frequency shift"

Question 5(b) OR [4 marks]

Explain PPI Display method for RADAR

Answer:

PPI (Plan Position Indicator) shows **top view** of RADAR coverage area with range and bearing information.

Display Features:

• Circular screen: Center represents RADAR location

• Rotating trace: Synchronized with antenna rotation

• Range rings: Concentric circles for distance

• Bearing scale: 0-360° around circumference

Operation:

• **Sweep rotation**: Matches antenna rotation

• **Echo intensity**: Controls brightness

• Persistence: Afterglow maintains target visibility

• Range scale: Selectable range settings

Applications:

• Air traffic control: Aircraft positioning

• Marine navigation: Ship and obstacle detection


• Weather monitoring: Storm tracking

Mnemonic: "PPI Provides Position Information Perfectly"

Question 5(c) OR [7 marks]

Draw the block diagram of Pulse radar and explain the working principle.

Answer:



Working Principle:

Transmission:

• Master oscillator: Generates RF carrier

• Modulator: Creates short pulses

• Power amplifier: Amplifies pulse power

• Duplexer: Routes pulse to antenna

Reception:

- **Echo reception**: Antenna receives reflected signals
- RF amplification: Low noise amplification
- Mixing: Converts to intermediate frequency
- IF amplification: Further amplification
- **Detection**: Extracts video signal
- **Display**: Shows range vs amplitude

Key Parameters:

- Pulse width: Determines range resolution
- PRF: Pulse repetition frequency
- **Peak power**: Maximum range capability
- **Duty cycle**: Average power consideration

Advantages:

- **High peak power**: Long range capability
- Good range resolution: Narrow pulses
- Simple processing: Direct detection

Mnemonic: "Pulse RADAR Pulses Powerfully for Precise Position"